

Truss Clip

Application and Design Features

The Sabrefix Truss Clip attaches trusses and rafters to wall plates to provide wind restraint. Avoids skew nailing damage and provides positive resistance to wind forces. Fix wall plate with Sabrefix 2.5 1200mm o/a bent 100mm wall plate strap.

Material Specification

0.9mm pre-galvanised mild steel to BS EN 10142 DX51D Z275



Issue February 2005

Product Reference	Dimensions		Fixings		Safe Working Loads (kN)	
	Truss Width	Clip Width	rus	Wall Plate	Lateral	Short Term Uplift
SABTC-38	35	38	6	6	0.45	2.05
SABTC-44	41	44	6	6	0.45	2.05
SABTC-50	47	50	6	6	0.45	2.05

General Notes

1 Safe Working Loads are based on load tests conducted at TRADA Technology Ltd.

Tests carried out by Brighton Polytechnic Department of Civil Engineering

2 3.75x30mm sherardised square twist nails must be used to achieve the stated safe working loads

sabrefix
THE QUALITY SUPPLIER OF BUILDERS METALWORK

Sabrefix Thrextan Road Industrial Estate, Watton, Norfolk IP25 6NG
T: 01953 883919 F: 01953 884229 E:sales@sabrefix.co.uk © Sabrefix

QUALITY PRODUCTS • QUALITY SERVICE