

Mini Joist Hanger

Application and Design Features

SABJHMH Mini Hanger is a compact hanger to support short span joists, trap hatches and in-fill timbers in roof space. Designed for fast and economical light duty applications.

Fixing Instructions

Use 3.75mmx30mm sheridised square twisted nails in all holes

Material Specification

0.9mm pre-galvanised mild steel to BS EN 10142 DX51D Z275



Issue February 2005

Product Reference	Dimensions			Joist Size
	Width	Height	Bearing	
SABJHMH-38	38	71	45	35x75-100mm
SABJHMH-44	44	68	45	44x75-100mm
SABJHMH-50	50	65	45	50x75-100mm

Fixings		Safe Working Loads (kN)		
Joist	Front	Uplift	Medium Term	Long Term
8	8	0.8	3.2	3.2
8	8	0.8	3.2	3.2
8	8	0.8	3.2	3.2

General Notes

- 1 Safe Working Loads are based on load tests conducted at TRADA Technology Ltd.
Tests carried out by Brighton Polytechnic Department of Civil Engineering
- 2 3.75x30mm sherardised square twist nails must be used to achieve the stated safe working loads



Sabrefix Threxton Road Industrial Estate, Watton, Norfolk IP25 6NG
T: 01953 883919 F: 01953 884229 E:sales@sabrefix.co.uk © Sabrefix